

Duplexor DPU-33

	UHF DUPLEXERS				
FREQUENCY RANGE [MHZ]	A (405-435)	B (435-455)	C (450-475)	D (470-495)	E (490-515)
TX/RX SEPARATION MIN. [MHZ]	5.0(>4.5)	5.0(>4.5)	5.0(>4.5)	5.0(>4.5)	5.0(>4.5)
CONTINUOUS POWER INPUT, MAX. [W]	50	50	50	50	50
INSERTION LOSS TX/ANTENA, MAX [DB]	1.3	1.3	1.3	1.3	1.3
INSERTION LOSS RX/ANTENA, MAX [DB]	1.3	1.3	1.3	1.3	1.3
IMPEDANCE [Ω]	50	50	50	50	50

TX NOISE REJECTION AT RX FREQ. [DB]	90typ, 80min	90 typ, 80min	90 typ, 80min	90 typ, 80min	90 typ, 80min
RX/TX ISOLATION AT TX FREQ. [DB]	90typ, 80min	90typ, 80min	90typ, 80min	90typ, 80min	90typ, 80min
RL [DB]	-23max, -27typ	-23max, -27typ	-23max, -27typ	-23max, -27typ	-23max, -27typ
CONNECTORS STANDARD/OPTIONAL TYPE	N/BNC-TNC (f)	N/BNC-TNC (f)	N/BNC-TNC (f)	N/BNC-TNC (f)	N/BNC-TNC (f)
TEMPERATURE RANGE [°C]	-30 to +60	-30 to +60	-30 to +60	-30 to +60	-30 to +60
NUMBER OF CAVITIES	6	6	6	6	6